

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



TMCX2002L 2" ALCRI GLND (16 5-29 9MM)

Crouse-Hinds	CBL GLND (16.5-29.9IVIIVI)	
Catalog Number	TMCX2002L	
Manufacturer	Crouse-Hinds	
Description	Eaton Crouse-Hinds Series Terminator Ii TMCX Cable Gland, Liquid Compound, Cable Range:1.81-2.72", Cable Sealing:2 (M), Metal-Cladcorrugated Armoured, Teck Armoured, Armoured Barrier and Tray Cable, Armoured Gland, Aluminum, 2" NPT	
Weight per unit	12.5 (lbs/each)	
Product Category	BX, MC, Armored Cable Fittings	
Features		
connection	Cable OD 1.81 to 2.72 inch	
dimensions	6.8800 IN X 4.9800 IN X 4.9800 IN	
Material, Color, and Finish		
Color	Natural with red union nut	
Finish	Untreated	
Dimensions and Weight		
Size	2 IN NPT Size 2	
Descriptions		
Description	2" AL CBL GLND (16.5-29.9MM)	
extra long description	CRS-H TMCX200 2 L BARR GLAND 2 NPT	
Features	TMCX II explosionproof cable glands from Eaton Crouse-Hinds Division are used to terminate armoured barrier, non-armoured barrier and TECK armoured cable in hazardous locations. Its unique design features, coupled with our fast curing Chico LiquidSeal compound, make the TMCX II the easiest and safest	

	solution available.
Long Description	Eaton Crouse-Hinds series Terminator II TMCX cable gland, Liquid
	compound,Cable Range:1.81-2.72",Cable Sealing:2
	(M),Metal-cladcorrugated armoured,TECK armoured,armoured

barrier and tray cable, Armoured gland, Aluminum, 2" NPT Product Type Barr Gland 2 NPT SZ2 Alu Liq 2 Piece Union Design Special Features

Manufacturer Information

Brand	Eaton
GTIN	00662276440296
Manufacturers Part Number	TMCX200 2 L
UPC	662276440296



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies,	Classificat	ions, and	Categories
-------------	-------------	-----------	------------

Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Cable gland

Packaging

ckayırıy		
Carton	1	
Weight Per each	12.52	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	2 inch NPT
standard	UL and cUL Class 1, Div 1 (ABCD) Class 2 (EFG)
Temperature Rating	-40 to + 60 Degrees C