


# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





## **TPJ2LA Trademaster Wallplate Jumbo 2G 2 Toggle La** Pass & Seymour/Legrand

e	
Catalog Number	TPJ2LA
Manufacturer	Pass & Seymour/Legrand
Description	Trademaster Jumbo Wall Plate, Double Gang, Toggle Plate Is Molded Of Rugged, Practically Indestructible Self-Extinguishing Nylon. It Is Preferred For Hospital, Industrial, Institutional, and Other High-Abuse Applications. Available In Ivory, White, Brown,
Weight per unit	Gray, Black, Blue, Orange, Red, and Light Almond. 0.1077 (lbs/each)
Product Category	,
Features	
cutout	Toggle
indoor/outdoor	Indoor
insulation	Bare
Mounting Type	
Number of Gangs	2
orientation	Vertical
Wall Plate Type	T 1.0 % I
Material, Color, and Finish	
Finish	Matte
Dimensions and Weight	
Size	4.9 in
Thickness	0.07
Descriptions	
Construction	Plastic
Description	TRADEMASTER WALLPLATE JUMBO 2G 2 TOGGLE LA
extra long description	P&S TPJ2LA TRADEMASTER WP JUMBO 2G
Long Description	Trademaster Jumbo Wall Plate, double gang, toggle plate is molded of rugged, practically indestructible self-extinguishing nylon. It is preferred for hospital, industrial, institutional, and other high-abuse applications. Available in Ivory, White, Brown, Gray, Black, Blue, Orange, Red, and Light Almond.
Product Type	Trademaster WP Jumbo 2G 2TOG La
Special Features	Molded of rugged, indestructible self extinguishing nylon



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

N	lanut	facturer	Inform	nation
		4014.01		

Brand	Pass and Seymour
GTIN	00785007025194
Manufacturers Part Number	TPJ2-LA
UPC	785007025194

## **Taxonomies, Classifications, and Categories**

Category Description	Residential plates
Type	Wall Plate

#### **Packaging**

Carton	20
Package	200
Weight Per each	0.1077

### Uses, Certifications, and Standards

Application	Residential/Commercial
Mounting	WALL
standard	CULUS, CSA, UL514