

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

TPJ8 Trademaster Wallplate Jumbo	1G 1	Duplex BN
Pass & Seymour/Legrand		•

Pass & Seymour/Legrand	J	
Catalog Number	TPJ8	
Manufacturer	Pass & Seymour/Legrand	
Description	Trademaster, Single Gang, Duplex, Jumbowall Plate In Whiteis Molded Of Rugged, Practically Indestructible Self-Extinguishing Nylon. It Is Preferred For Hospital, Industrial, Institutional, and Other High-Abuse Applications. Available In Ivory, White, Brown, Gray, Black, Blue, Orange, Red, and Light Almond.	
Weight per unit		
Product Category		
Features		
cutout	Receptacle	
indoor/outdoor	Indoor	
insulation	Bare	
Mounting Type	Strap Mounted	
Number of Gangs	1	
orientation	Vertical	
Wall Plate Type		
Material, Color, and Finish Finish	Matte	
Dimensions and Weight		
Size	4.9 in	
Thickness	0.07	
Descriptions		
Construction	Plastic	
Description	TRADEMASTER WALLPLATE JUMBO 1G 1 DUPLEX BN	
extra long description	P&S TPJ8 TRADEMASTER WP JUMBO 1G 1	
Long Description	Trademaster, single gang, duplex, jumbowall plate in whiteis molded of rugged, practically indestructible self-extinguishing nylon. It is preferred for hospital, industrial, institutional, and other high-abuse applications. Available in Ivory, White, Brown, Gray, Black, Blue, Orange, Red, and Light Almond.	
Product Type	Trademaster WP Jumbo 1G 1 Duplex BN	
Special Features	Molded of rugged, indestructible self extinguishing nylon	
··· p		



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

			er			

Brand	Pass and Seymour
GTIN	00785007025002
Manufacturers Part Number	TPJ8
UPC	785007025002

Taxonomies, Classifications, and Categories

Category Description	Residential plates
Туре	Wall Plate

Packaging

okugirig		
Carton	1	
Package	200	
Weight Per each	0.0631	

Uses, Certifications, and Standards

Application	Residential/Commercial
Mounting	WALL
standard	CULUS, CSA, UL514