

# Eaton TRL07

Catalog Number: TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure



## General specifications

**Product Name**  
Eaton TR timing relay

**UPC**  
786685313580

**Product Height**  
3.43 in

**Product Weight**  
0.16 lb

**Compliances**  
TUV  
CE Marked

**Catalog Number**  
TRL07

**Product Length/Depth**  
2.56 in

**Product Width**  
0.69 in

**Warranty**  
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

**Certifications**  
cULus Listed  
CSA Certified

## Product specifications

### Frequency rating

50-60 Hz

### Enclosure

IP40

### Enclosure material

Self-extinguishing plastic

### Contact configuration

SPDT

### Time delay

0.05 seconds-100 hours

### Series

TR

### Functions

Single shot leading or trailing edge voltage controlled and control input

ON delay control signal start

ON/OFF delay

Trailing edge OFF

Power triggered

Flasher-pause first

### Input voltage

24-240 Vac/dc

### Mounting method

Compact DIN rail

## Resources

### Specifications and datasheets

[Eaton Specification Sheet - TRL07](#)

# Eaton TRL07

Catalog Number: TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure



## General specifications

**Product Name**  
Eaton TR timing relay

**UPC**  
786685313580

**Product Height**  
3.43 in

**Product Weight**  
0.16 lb

**Compliances**  
TUV  
CE Marked

**Catalog Number**  
TRL07

**Product Length/Depth**  
2.56 in

**Product Width**  
0.69 in

**Warranty**  
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

**Certifications**  
cULus Listed  
CSA Certified

## Product specifications

### Frequency rating

50-60 Hz

### Enclosure

IP40

### Enclosure material

Self-extinguishing plastic

### Contact configuration

SPDT

### Time delay

0.05 seconds-100 hours

### Series

TR

### Functions

Single shot leading or trailing edge voltage controlled and control input

ON delay control signal start

ON/OFF delay

Trailing edge OFF

Power triggered

Flasher-pause first

### Input voltage

24-240 Vac/dc

### Mounting method

Compact DIN rail

## Resources

### Specifications and datasheets

[Eaton Specification Sheet - TRL07](#)