

Eaton TRL07

Catalog Number: TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure



General specifications

Product Name

Eaton TR timing relay

UPC

786685313580

Product Height

3.43 in

Product Weight

0.16 lb

Compliances

TUV

CE Marked

Catalog Number

TRL07

Product Length/Depth

2.56 in

Product Width

0.69 in

Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications

cULus Listed

CSA Certified

Product specifications

Frequency rating

50-60 Hz

Enclosure

IP40

Enclosure material

Self-extinguishing plastic

Contact configuration

SPDT

Time delay

0.05 seconds-100 hours

Series

TR

Functions

Single shot leading or trailing edge voltage controlled and control input

ON delay control signal start

ON/OFF delay

Trailing edge OFF

Power triggered

Flasher-pause first

Input voltage

24-240 Vac/dc

Mounting method

Compact DIN rail

Resources

Specifications and datasheets

[Eaton Specification Sheet - TRL07](#)

Eaton TRL07

Catalog Number: TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure



General specifications

Product Name

Eaton TR timing relay

UPC

786685313580

Product Height

3.43 in

Product Weight

0.16 lb

Compliances

TUV

CE Marked

Catalog Number

TRL07

Product Length/Depth

2.56 in

Product Width

0.69 in

Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications

cULus Listed

CSA Certified

Product specifications

Frequency rating

50-60 Hz

Enclosure

IP40

Enclosure material

Self-extinguishing plastic

Contact configuration

SPDT

Time delay

0.05 seconds-100 hours

Series

TR

Functions

Single shot leading or trailing edge voltage controlled and control input

ON delay control signal start

ON/OFF delay

Trailing edge OFF

Power triggered

Flasher-pause first

Input voltage

24-240 Vac/dc

Mounting method

Compact DIN rail

Resources

Specifications and datasheets

[Eaton Specification Sheet - TRL07](#)