



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## TRM6 250V 6A 1 1/2X13/32 Midget TD Fuse

*Mersen Fuses*

Catalog Number	TRM6
Manufacturer	Mersen Fuses
Description	Fuse TRM - Midget - Time-Delay 250VAC 6A Ferrule Tri-Onic®
Weight per unit	0.0120 (lbs/each)
Product Category	Small Dimension Fuses

### Features

AC Voltage Rating	250
amperage rating	6
class	Midget
connection	Ferrule
interrupt rating	10
Voltage Rating	250

### Material, Color, and Finish

Body Material	GMG
---------------	-----

### Dimensions and Weight

Size	1.5 x 0.41
------	------------

### Descriptions

Description	250V 6A 1 1/2X13/32 MIDGET TD FUSE
extra long description	Mersen TRM6 Fuse TRM - Midget - Tim
Features	Tri-Onic® TRM time-delay midget fuses are rated 250 volts AC and are offered in ampere ratings from 1/10 to 30A. They have 12 seconds time-delay at 200 rating to provide supplemental protection of small motors, small transformers and other high inrush loads, plus many other 250 volt applications. (Not for Branch Circuit Protection).
Long Description	Fuse TRM - Midget - Time-Delay 250VAC 6A Ferrule Tri-Onic®
Product Type	Fuse TRM - Midget - Time-Delay 250VAC 6A Ferrule
Short Description	250V 6A 1 1/2x13/32 MID TD
Special Features	Numerous ratings for a wide variety of applications 250VAC rating in all sizes up to 30A Time-delay for circuits with high inrush current Can be used with UltraSafe™ fuse holders 1 1/2" x 13/32" (10mm x 38mm) dimensions

### Manufacturer Information

Brand	Mersen
GTIN	00782001746483
Manufacturers Part Number	TRM6
UPC	782001746483



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	Midget Fuses

## Packaging

Carton	1
Package	10
Weight Per each	0.012

## Uses, Certifications, and Standards

Application	Small motors Small transformers Lighting circuits Control circuits
Mounting standard	Clip UL listed to standard 248-14 File E33925 CSA Certified to Standard C22.2 No. 248.14