Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

430 South Fletcher
75951-0000, TX Jasper
Phone: 409-489-0056
Fax: 409-489-0059



TY525M 7.31" "Ty-Rap" Cable Tie

Abb Installation Products, Inc

Catalog Number	TY525M
Manufacturer	Abb Installation Products, Inc
Description	Cable Tie, Natural Polyamide (Nylon 6.6) For Temperatures Up to 85 Degrees Celsius (185 F) For Indoor Applications, Ul/En/CSA62275 Type 2/21S Rated For Ah-2 Plenum and As A Flexible Cable and Conduit Support, Length Of 185.67MM (7.31 Inches), Width Of 4.9MM (0.19 Inches), Thickness Of 1.09MM (0.043 Inches), Tensile Strength Rating Of 222 Newtons (50 Pounds)
Weight per unit	0.0040 (lbs/each)
Product Category	Cable Ties & Wraps

Features

media	Yes
Tensile Strength	50

Dimensions and Weight

Length	7.2
Thickness	0.05
Width	0.19

Descriptions

Description	7.31" "TY-RAP" CABLE TIE
extra long description	TB TY525M CABLE TIE 50LB 7 NAT NYLO
Long Description	Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 185.67mm (7.31 Inches), Width of 4.9mm (0.19 Inches), Thickness of 1.09mm (0.043 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds)
Product Type	Cable Tie 50LB 7 Nat Nylon 2-PC Di
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
430 South Fletcher
75951-0000, TX Jasper
Phone: 409-489-0056
Fax: 409-489-0059

Manufacturer Information

Brand	Ty-Rap
GTIN	00786210805092
Manufacturers Part Number	TY525M
UPC	786210805092

Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Type	HIGH PERFORMANCE

Packaging

Carton	100
Package	1000
Weight Per each	0.004

Uses, Certifications, and Standards

standard	UL E49405