

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

TY529M 30" Ty-Rap Abb Installation Products, Inc

Catalog Number	TY529M
Manufacturer	Abb Installation Products, Inc
Description	Cable Tie, Natural Polyamide (Nylon 6.6) For Temperatures Up to 85 Degrees Celsius (185 F) For Indoor Applications, UI/En/CSA62275 Type 2/21S Rated For Ah-2 Plenum and As A Flexible Cable and Conduit Support, Length Of 770.61MM (30.34 Inches), Width Of 6.93MM (0.273 Inches), Thickness Of 1.52MM (0.06 Inches), Tensile Strength Rating Of 534 Newtons (120 Pounds)
Weight per unit	0.0180 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
Tensile Strength	120;530
Dimensions and Weight	
Length	30.34
Thickness	0.06
Width	0.273
Descriptions	
Description	30" TY-RAP
extra long description	ABB TY529M CBL TIE 120LB 30IN NATUR
Long Description	Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 770.61mm (30.34 Inches), Width of 6.93mm (0.273 Inches), Thickness of 1.52mm (0.06 Inches), Tensile Strength Rating of 534 Newtons (120 pounds)
Product Type	CBL Tie 120LB 30IN Natural Nylon
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time
Manufacturer Information	
Brand	······································
GTIN	00786210830735
Manufacturers Part Number	TY529M
UPC	786210830735



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps	
Туре	HIGH PERFORMANCE	
Availability		
minimum qty	50	
Packaging Carton		
Carton	50	
Package	500	
Weight Per each	0.018	
Uses, Certifications, and Stand	ards	

UL E49405