

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Taxonomies, Classifications, and Categories Category Description

UAG1400 1" Ua Sealtite Conduit, Bonded UI 400' *Southwire Company*

Catalog Number	UAG1400	
Manufacturer	Southwire Company	
Description	TITAN2 Type UI LFMC Is Manufactured With A Spiral Wound Strip Of Heavy Gauge Corrosion-Resistant Hot-Dipped Galvanized Steel. For 3/8" Through 1-1/4" Trade Sizes The Core Is Constructed With A Square Locked Steel Strip With An Integral Copperbonding Strip Enclosed Within The Steel Convolutions. Fo 1-1/2" Through 4" Trade Sizes The Core Is Constructed With A Fully Interlocked Steel Strip. A Rugged Flame Retardant Flexible PVC Jacket Is Extruded Over The Steel Core. The Grey Jacket Resists Oils Mild	
Weight per unit	0.6000 (lbs/ft)	
Product Category	Conduit & Raceways	
atures		
outside diameter	1305	
mensions and Weight		
Length	400	
scriptions		
Description	1" UA SEALTITE CONDUIT, BONDED UL 400'	
extra long description	SWC 55093004 Titan2 Type UL Liquidt	
Long Description	Titan2 Type UL LFMC is manufactured with a spiral wound strip of heavy gauge corrosion-resistant hot-dipped galvanized steel. For 3/8" through 1-1/4" trade sizes the core is constructed with a square locked steel strip with an integral copperbonding strip enclosed within the steel convolutions. For 1-1/2" through 4" trade sizes the core is constructed with a fully interlocked steel strip. A rugged flame retardant flexible PVC jacket is extruded over the steel core. The grey jacket resists oils mild	
Product Type	TITAN2 Type UI Liquidtight Flexible Metal Conduit	
anufacturer Information		
Brand	Flexible Conduit	
GTIN	00032886042447	
Manufacturers Part Number	55093004	
UPC	032886042447	

Liquid Tight



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size		
Trade Size	1	
Packaging		
Carton	400	
Weight Per foot	0.6	