

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

UAG38 3/8" Ua Sealtite Conduit. Bonded III 100'

Catalog Number	UAG38		
Manufacturer	Southwire Company		
Description	TITAN2 Type UI LFMC Is Manufactured With A Spiral Wound Str Of Heavy Gauge Corrosion-Resistant Hot-Dipped Galvanized Steel. For 3/8" Through 1-1/4" Trade Sizes The Core Is Constructed With A Square Locked Steel Strip With An Integral Copperbonding Strip Enclosed Within The Steel Convolutions. F 1-1/2" Through 4" Trade Sizes The Core Is Constructed With A Fully Interlocked Steel Strip. A Rugged Flame Retardant Flexible PVC Jacket Is Extruded Over The Steel Core. The Grey Jacket Resists Oils Mild		
Weight per unit	0.2400 (lbs/ft)		
Product Category			
atures			
outside diameter	700		
mensions and Weight			
Length	100		
escriptions			
Description	3/8" UA SEALTITE CONDUIT, BONDED UL 100'		
extra long description	SWC 55092903 Titan2 Type UL Liquidt		
Long Description	Titan2 Type UL LFMC is manufactured with a spiral wound strip of heavy gauge corrosion-resistant hot-dipped galvanized stee For 3/8" through 1-1/4" trade sizes the core is constructed with a square locked steel strip with an integral copperbonding strip enclosed within the steel convolutions. For 1-1/2" through 4" trade sizes the core is constructed with a fully interlocked stee strip. A rugged flame retardant flexible PVC jacket is extruded over the steel core. The grey jacket resists oils mild		
Product Type	TITAN2 Type UI Liquidtight Flexible Metal Conduit		
anufacturer Information			
Brand	Flexible Conduit		
GTIN	00032886042690		
Manufacturers Part Number	55092903		
UPC	032886042690		

Category Description Liquid Tight

LTM-UL



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

rrage Size		
Trade Size	3/8	
Packaging		
Carton	100	
Weight Per foot	0.24	