

## **E**LLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## UL112150 1-1/2" Ua Sealtite Conduit, Bonded UI 150' Southwire Company

Catalog Number	UL112150	
Manufacturer	Southwire Company	
Description	TITAN2 Type UI LFMC Is Manufactured With A Spiral Wound Strip Of Heavy Gauge Corrosion-Resistant Hot-Dipped Galvanized Steel. For 3/8" Through 1-1/4" Trade Sizes The Core Is Constructed With A Square Locked Steel Strip With An Integral Copperbonding Strip Enclosed Within The Steel Convolutions. For 1-1/2" Through 4" Trade Sizes The Core Is Constructed With A Fully Interlocked Steel Strip. A Rugged Flame Retardant Flexible PVC Jacket Is Extruded Over The Steel Core. The Grey Jacket Resists Oils Mild	
Weight per unit	1.1 (lbs/ft)	
Product Category	Conduit & Raceways	
Features		
outside diameter	1882	
Dimensions and Weight		
Length	150	
Descriptions		
Description	1-1/2" UA SEALTITE CONDUIT, BONDED UL 150'	
extra long description	SWC 55093201 Titan2 Type UL Liquidt	
Long Description	Titan2 Type UL LFMC is manufactured with a spiral wound strip of heavy gauge corrosion-resistant hot-dipped galvanized steel. For 3/8" through 1-1/4" trade sizes the core is constructed with a square locked steel strip with an integral copperbonding strip enclosed within the steel convolutions. For 1-1/2" through 4" trade sizes the core is constructed with a fully interlocked steel strip. A rugged flame retardant flexible PVC jacket is extruded over the steel core. The grey jacket resists oils mild	
Product Type	TITAN2 Type UI Liquidtight Flexible Metal Conduit	
Manufacturer Information		
Brand	Flexible Conduit	
GTIN	00032886042980	
Manufacturers Part Number	55093201	
UPC	032886042980	
Taxonomies, Classifications, and (	Categories	
Category Description	-	



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size Trade Size	1 1/2	
Packaging	150	
Carton Weight Per foot		