



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1615 North Hazel St.
71801-0000, AR Hope
Phone: 870-777-4225
Fax: 870-777-4343



UNF100NR 1-In Female Union

Appleton/Oz Gedney

Catalog Number	UNF100NR
Manufacturer	Appleton/Oz Gedney
Description	Unilets Unf Union, Trade Size: 1 In, Outside Diameter: 2 In, Length: 1.72 In, Flexibility: Rigid and Imc, Material: Steel, Connection: Female Threaded, Finish: Zinc Electroplate, Standard: UI 886 (1203), UI File Number E10444, UI Listed
Weight per unit	0.4700 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

connection	Female Threaded
outside diameter	2

Dimensions and Weight

Length	1.72
--------	------

Descriptions

Description	1-IN FEMALE UNION
extra long description	APP UNF100NR 1 UNION CONNECTOR TYPE
Long Description	UNILETS UNF Union, Trade Size: 1 IN, Outside Diameter: 2 IN, Length: 1.72 IN, Flexibility: Rigid And IMC, Material: Steel, Connection: Female Threaded, Finish: Zinc Electroplate, Standard: UL 886 (1203), UL File Number E10444, UL Listed
Product Type	1 Union Connector Type Unf
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity;Concentric ring interlocked design sizes makes possible smaller diameter, allowing use in tighter spaces;Explosionproof, dust-ignitionproof;Smooth, rounded integral bushing in each hub protects conductor insulation;UNF unions are used for joining conduit and connecting conduit to enclosures, Facilitates modifications, permits removal of enclosures without turning or removal of conduit

Manufacturer Information

Brand	Appleton/Oz Gedney
GTIN	00781381234146
Manufacturers Part Number	UNF100NR
UPC	781381234146

Taxonomies, Classifications, and Categories

Category Description	COUPLINGS, ADAPTERS, REDUCERS, BUSHINGS, & CAPS
Type	UNF Union



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1615 North Hazel St.
71801-0000, AR Hope
Phone: 870-777-4225
Fax: 870-777-4343

Trade Size

Trade Size 1

Packaging

Carton 1

Weight Per each 0.47

Uses, Certifications, and Standards

Application For Connecting Conduit To Conduit
standard and Class III, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181
..... Certified; Class II, Groups E, F, G; UL 886 (1203), UL File Number
..... E10444, UL Listed for Class I, Groups A, B, C, d